

## Filtre apa Cintropur



Denumire filtru	NW18	NW25	NW32	TIO	NW25 DUO-CTN	NW25 TE-CTN	NW32 TE
Racord	3/4"	3/4" / 1"	1 1/4"	1"	3/4" + 1"	1"	1 1/4"
Debit nominal $\Delta P=0.2\text{bar}$	3.5 m <sup>3</sup> /h	5.5 m <sup>3</sup> /h	6.5 m <sup>3</sup> /h	0.5 m <sup>3</sup> /h	0.5 m <sup>3</sup> /h	0.5 m <sup>3</sup> /h	0.5 m <sup>3</sup> /h
Presiune de lucru	10 bar	10 bar	10 bar	10 bar	10 bar	10 bar	10 bar
Presiune maxima de operare	16 bar	16 bar	16 bar	16 bar	16 bar	16 bar	16 bar
Temperatura maxima de operare	50 °C	50 °C	50 °C	50 °C	50 °C	50 °C	50 °C
Greutate	0.9 kg	1.2 kg	1.7 kg	1.8 kg	2.4 kg	1.3 kg	1.6 kg
Finete de filtrare manson	25µ	25µ	25µ	25µ	25µ	-	-
Volum carbune	-	-	-	0.57 l	0.57 l	0.57 l	1.7 l
Suprafata de filtrare	190 cm <sup>2</sup>	450 cm <sup>2</sup>	840 cm <sup>2</sup>	335 cm <sup>2</sup>	1x450 cm <sup>2</sup>	-	-