

Produs

Sterilizatoare UV Eurotrol



MODEL	FC-8	FC-12	FC-15	FC-20	FC-24	FC-35	FC-45
Debit maxim	1810 l/h	2720 l/h	3400 l/h	4536 l/h	5443 l/h	7938 l/h	10200 l/h
Putere [W]	29	40	65	65	80	100	120
Racord ["]	3/4"	1"	1"	1 1/2 "	1 1/2 "	2"	2"
Dimensiuni mm]	114 x 710	133 x 940	133 x 940	160 x 940	160 x 940	160 x 1235	160 x 1235
Temperatura	5-40°C	5-40°C	5-40°C	5-40°C	5-40°C	5-40°C	5-40°C
Presiune [bar]	1-10	1-10	1-10	1-10	1-10	1-10	1-10
Material	AISI304	AISI304	AISI304	AISI304	AISI304	AISI304	AISI304
Alimentare	230V/50Hz	230V/50Hz	230V/50Hz	230V/50Hz	230V/50Hz	230V/50Hz	230V/50Hz

Produs

Lampi de schimb si teci de quart



Model Sterilizator UV	Lampa UV	Teaca de quart
FC8	T529 (D.18 x L.630mm)	D.24,5 x L.680mm
FC12	T540 (D.18 x L.850mm)	D.24,5 x L.910 mm
FC15	T565 (D.18 x L.850mm)	D.24,5 x L.910 mm
FC20	T565 (D.18 x L.850mm)	D.24,5 x L.910 mm
FC24	T680 (D.23 x L.850mm)	D.30 x L.910 mm
FC35	T6100 (D.23 x L.1160mm)	D.30 x L.1205 mm
FC45	T6120 (D.18 x L.1150mm)	D.24,5 x L.1205 mm

*Lampa UV se va inlocui la 9000-10000 ore de functionare (aproximativ 12 luni)

** Teaca de quart se recomanda sa se curete la fiecare 6-12 luni