



“For sediment filtration that makes the grade.”

Hyper Filtration Media

Turbidex’s enhanced ability to remove sediment results in superior water clarity and down stream cost savings on chemicals, filter cartridges, membrane cleaning, membrane life, etc.

Higher Flow Rates

Because of it’s high porosity and hydrophylic nature, Turbidex can typically operate at higher service flow rates than multimedia or conventional sand filters.

Water Savings

Customers that switch to Turbidex report that the pressure drops across the system decrease substantially. This results in longer service runs and less frequency between backwashes.

Easier to Inventory and Install

Turbidex is less expensive to ship because it only weighs 50 lbs. per cubic foot. With one part number and one media it is much simpler to order, inventory and install.

Turbidex™ is a unique natural ore called clinoptilolite that has many outstanding advantages over common granular filter sands and multimedia used for suspended solids reduction. Viewed under an electron scanning microscope, the granules reveal an angular shape, rough surface and microporous void spaces as small as 3 microns. This creates a surface area over 100 times greater than silica sand. The angularity of the granules and the tapered internal pore spaces allow for reduction of dirt, silt and organic matter suspended in water by bridging, straining and adhesion. The rough surface and internal porosity provide a high surface area for efficient reduction of suspended matter. Utilizing deep bed filtration can typically reduce suspended solids down to the 5 micron or less range. Turbidex’s structure typically creates less pressure loss through the filter and allows deeper sediment penetration into the bed for higher sediment loading and longer filter runs. The deep bed filtration capacity of

Turbidex prevents a rapid buildup of head loss and blinding problems that are associated with typical sand filters. The longer filter run times reduce backwash frequency, which provides conservation of water. This ideal combination of particle shape, texture and porosity make it a good choice where quality water filtration and water conservation are important.

Substantial savings can be realized when designing a system using Turbidex. Its low pressure drop, high service flow rates and high bed loadings combined with lower backwash frequency allow economy in equipment downsizing and reduced pumping requirements. Its low density also saves on handling expense and shipping costs.

Turbidex can be applied to systems designed for either pressure or gravity flow. Because of its unique physical characteristics, Turbidex can be used to replace multimedia (graded density) filter designs.

ADVANTAGES

- Deep bed filtration results in superior water quality and reduces the load on downstream equipment.
- High sediment removal capacity results in longer filter runs, with a substantial savings in backwash water and time out of service.
- High service flow rates result in lower equipment costs and a savings in space.
- Reduced shipping cost due to lighter weight/cu.ft.
- Replacement of multimedia with Turbidex in existing installations may increase filter capacity.
- Turbidex is an all-natural, environmentally safe product.


PHYSICAL PROPERTIES

- Color: Light tan to near white
- Dry Bulk Density: 50 lbs/cu.ft
- Specific Gravity: 2.2 g/cc
- Mesh Size: 14x30
- Effective Size: 0.55mm
- Uniformity Coefficient: 1.8
- Hardness: 4-5 (Mohs Scale)


CONDITIONS FOR OPERATION

- Water pH: Wide range
- Max. Water Temp.: 140°F/60°C
- Bed Depth: 24-36 inches
- Freeboard: 50% of bed depth
- Backwash Flow Rate: 15-20 gpm/sq.ft.
- Backwash Bed Expansion: 30-40% of bed depth
- Service Flow Rate: 12-20 gpm/sq.ft.
- Local conditions may require lower flow rates
- A gravel support bed is required
- Allow bed to saturate before initial backwash

Service Flow Pressure Drop



Backwash Bed Expansion



Certified to NSF/ANSI Standard 61

ORDER INFORMATION

Part No.	Description	Cu. Ft./Bag	Wt./Cu. Ft.*	Bags/Pallet	Weight/Pallet	Pallet Dimensions
A8025	Turbidex™	1	50 lbs.	40	2050 lbs.	40" x 48" x 44"

*Weight per cubic foot is approximate.

The information and recommendations in this publication are based on data we believe to be reliable. They are offered in good faith, but do not imply any warranty or performance guarantee, as conditions and methods of use of our products are beyond our control. As such, Hydro Source, LLC. makes no express or implied warranties of any kind with respect to this product, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. We recommend that the user determine whether the products and the information given are appropriate, and the suitability and performance of our products are appropriate, by testing with its own equipment. Specifications are subject to change without notice.

The information and recommendations given in this publication should not be understood as recommending the use of our products in violation of any patent or as a license to use any patents of Hydro Source, LLC.

The filter medias listed in this brochure do not remove or kill bacteria. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Hydro Source, LLC. will not be liable under any circumstance for consequential or incidental damages, including but not limited to, lost profits resulting from the use of our products.

CALIFORNIA PROPOSITION 65 WARNING: This product contains crystalline silica which is known to the State of California to cause cancer and other substances which are known to the State of California to cause cancer, birth defects and reproductive harm.

HYDRO SOURCE, LLC

1501 N 28th Street Harlingen, TX 78550

956-425-1110

www.turbidex.com

North American Distributor:



4462 Duraform Lane • Windsor, WI 53598

(608) 846-3010 • www.clackcorp.com